

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION	
Identity (As Used on Label and List): Multi-Clean Multi-Stat Maintainer Product Class: Water-borne floor polish Emergency Telephone Number: 800-255-3924 Telephone Number for Information: 651-481-1900 Manufacturer's Name and Address: Multi-Clean®, A Division of Minuteman International, Inc. 600 Cardigan Road Shoreview, MN 55126	
SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS	
Hazardous Components (Specific Chemical Identity):	
Chemical	Common Name(s) %
A	Emulsified acrylic polymer (proprietary) 5 - 15
B	Diethylene glycol monoethyl ether CAS #111-90-0 1 - 5
C	Dipropylene glycol methyl ether CAS #34590-94-8 1 - 5
D	Water CAS #7732-18-5 80 - 100
SECTION III - HAZARDS IDENTIFICATION	
Emergency Overview	
Appearance and Odor: Milky pink liquid, mild acrylic odor Primary Hazards: Irritant	
Potential Health Hazards	
Route(s) of Entry: Skin Absorption: X Ingestion: X Inhalation: X Eye: May cause irritation on contact. Skin: May cause irritation on prolonged or repeated contact. Ingestion: May be harmful if swallowed. Inhalation: No effects expected. Signs and Symptoms of Exposure: Irritation on direct contact. Carcinogenicity: NTP? No OSHA Regulated? No IARC Monographs? No	
Target Organ (s): Skin, eyes, respiratory system. See Health Hazards Chronic. Medical Conditions Generally Aggravated by Exposure: N. Av. Health Hazards, Chronic: Overexposure to Dipropylene glycol methyl ether or its components has apparently been found to cause the following effects in laboratory animals, liver abnormalities and kidney damage.	
SECTION IV - FIRST AID MEASURES	
Emergency and First Aid Procedures:	
If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. Eye Contact: Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse. Inhalation: If ill effects occur from breathing vapors, remove victim to fresh air, quite, keep warm and contact physician. Sources Used: Raw material data, general toxicology from the trade for similar products.	
SECTION V - FIRE FIGHTING MEASURES	
Flammability: No Autoignition Temperature: N. Av. Flash Point (method used): None Flammable Limits: N. Av. LEL UEL Extinguishing Media: N. Av. Water? Foam? Water Fog? Alcohol Foam? CO₂? Dry Chemical? Vaporizing Liquid? Other?	
Special Fire Fighting Procedures: N. Av. Unusual Fire and Explosion Hazards: N. Av. TDG Flammability Classification: Non-flammable Sensitivity to Mechanical Impact: None Sensitivity to Static Discharge: None	
SECTION VI - ACCIDENTAL RELEASE MEASURES	
Steps to be Taken in Case Material is Released or Spilled: Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.	
SECTION VII - HANDLING AND STORAGE	
Precautions to be Taken in Handling and Storing: Storage Temperature: Minimum 40°F (4°C); Maximum 100°F (38°C) Other Precautions: Keep out of reach of children. Keep from freezing.	
SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION	
Respiratory Protection (Specify Types): Not required Ventilation: Local Exhaust: Not required Special: Not required Mechanical (General): Normal good ventilation sufficient. Other: Not required	
Protective Gloves: Natural rubber or synthetic. Eye Protection: Approved safety goggles or glasses. Footwear: Not required Other Protective Clothing or Equipment: Not required Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals.	

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: Approximately 212°F Specific Gravity (H₂O) = 1: 1.020 Vapor Density (Air = 1): > 1 Evaporation Rate (Butyl Acetate = 1): N. Av. Solubility in Water: Complete Vapor Pressure (MM HG): N. Av. Melting Point: N. Ap.	pH: 9 % Volatile: 90 - 95 Odor Threshold: N. Av. Oil/Water Distribution Coefficient: N. Av.				
SECTION X - STABILITY AND REACTIVITY					
Stability: Unstable: Stable: X Conditions to Avoid: N. Ap. Incompatibility (materials to avoid): N. Av. Hazardous Decomposition or By-products: N. Av. Hazardous Polymerization: May occur: Will not occur: X Conditions to Avoid: N. Ap.					
SECTION XI - TOXICOLOGICAL INFORMATION					
Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	N. Ap.	N. Ap.	N. Av.	N. Av.	N. Av.
B	N. Ap.	N. Ap.	N. Av.	5,000 mg/kg (rat, oral)	> 200mg/L (1 hr.)
C	100 ppm	100 ppm	N. Av.	5.6 gm/kg (rat, oral)	> 33,000 ppm (rat)
D	None	None	N. Av.	N. Av.	N. Av.
Teratogen, Mutagen, Reproductive Toxin Status: No Toxicologically Synergistic Products: N. Av.					
SECTION XII - ECOLOGICAL INFORMATION					
Ecotoxicological Information: N. Av. Chemical Fate Information: N. Av.					
SECTION XIII - DISPOSAL CONSIDERATIONS					
Waste Disposal Method: Solution may contain zinc. Coagulate with ferric chloride or sulfate and then lime. Decant the clear liquid to a sewer. Dispose of the coagulum by sanitary landfill or incinerator. Follow all existing pollution control ordinances. RCRA Hazard Class: None					
SECTION XIV - TRANSPORT INFORMATION					
Shipping Classification: Buffing or polishing compound UN Number: N. Ap. Packing Group: N. Ap.					
SECTION XV - PREPARATION DATA					
Prepared By: Mike Tarvin Telephone Number: 651-481-1900 Date: 10/06					
SECTION XVI - REGULATORY INFORMATION					
US Federal Regulations TSCA Status: All ingredients listed. CERCLA Reportable Quality: None SARA Title III Section 302 Extremely Hazardous Chemicals: None Section 311/312 Hazard Category: Immediate health hazard Section 313 Toxic Chemicals: Dipropylene glycol methyl ether (glycol ether) and Ethylene glycol monoethyl ether (glycol ether) State Regulations NOTICE STATE OF CALIFORNIA Warning: This product may contain chemicals known to the State of California to cause cancer or reproductive defects as trace impurities in the standard industrial materials used in the manufacture of this product. International Regulations WHMIS Controlled Product Hazard Class: D2B					
SECTION XVII - OTHER INFORMATION					
None N. Ap. - Not Applicable; N. Av. - Not Available					

NFPA SYSTEM

1 A. Health Hazard 0 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.